



Fast & Silent Motion

- Lightning Speed : MAX. 360°/sec
- Smooth Manual Speed : MIN. 0.05°/sec
- Endless 360° Pan Rotation
- Lowest Noise & Vibration
- Shortest Path by Vector Drive Technology
- High Accuracy with Micro-Stepping

Superior Zoom Camera

- X260 Zoom Control (Optical X26, Digital X10)
- Day & Night (IR Cut Filter)

Powerful Functions

- 128 Preset Positions with Alphanumeric Labels
- Pattern, Swing and Group Functions
- Privacy Zone
- Sensor In/Out (8 Input / 4 Output)
- Small Size (214mm Diameter)
- IP66 Weather proof and Built-in Fan & Heater
- Network Video Function (Optional)

Model		NTSC-26
Signal Format		NTSC
Camera	Image Device	1/4" Sony Super HAD CCD
	Effective Pixel	380K Pixels [768(H) x 494(V)]
	H. Resolution	480 TV Lines
	S/N Ratio	More than 48dB (AGC OFF)
	Zoom	x26 Optical Zoom and x10 Digital Zoom
	Focal Length	F1.6, f=3.5~91mm
	Min. Luminance	1.0 Lux (Day) / 0 Lux (Night, IR LED ON)
	Day & Night (ICR)	Auto / Day / Night (Mechanical IR Cut Filter)
	Focus	Auto / Manual
	Iris	Auto
	White Balance	Auto / Manual / Indoor / Outdoor
BLC	On / Off	
Pan/Tilt	Range	Pan : 360° (Endless) / Tilt : 90°
	Pan/Tilt Speed	Preset : 360°/sec
		Manual : 0.05° ~ 160°/sec (Zoom Proportional)
		Swing : 15° ~ 60°/sec (Zoom Proportional)
	Preset	128 Presets
	Pattern	4 Patterns (Max. 1 Minute Each)
	Swing	8 Swings
	Group	8 Groups (Max. 20 Entries)
Other Functions	Auto Flip, Auto Parking, Power Up Action	
General	Communication	RS-485
	Protocol	Pelco-D, Pelco-P Selectable
	Privacy Zone	8 Zones
	Sensor In/Out	8 Input / 4 Output (Optional)
	OSD	Menu / PTZ Info.
	Fan/Heater	Built-in
	Power	AC 24V / 2A
	Dimension - Dome	Dome : 152mm (Dm)
	Dimens. - Housing	214mm(Dm) X 260mm(H) / 8.42"(Dm) X 10.23"(H)
	Weight	Approx. 2.5Kg / 5.5Lbs
Operating Temp.	-30C ~ 50C / -22F ~ 122F	

* Specification & Design are subject to change without prior notice



3 Dimension Controller (Optional)

